

130mm


10mm


QUAD FOLD CART ASSEMBLY INSTRUCTIONS


! WEIGHT CAPACITY 110 KGS


WARNING: THIS CART IS NOT DESIGNED FOR TRANSPORTING CHILDREN/ADULTS.


WARNING: Please be aware some vinyl and indoor hard floor surfaces may be damaged or stained by the wheels from this cart. It is recommended they are not stored on some vinyl and indoor hard floor surfaces as these are for outdoor use only.


- 


1. Remove cart from carton.
- 


2. Release the fastening straps from base board.
- 


3. Remove base board from cart.
- 


4. Push down centre strap loop area to unfold cart.
- 


5. Gently push the front swivel wheels into the shaft. You will hear a click when it locks into place. Do not force the wheels into place as there is a risk that the lock button could get damaged.
- 


6. Gently push back wheels into shaft until it clicks in securely. You will hear a click when it locks into place. Do not force the wheels into place as there is a risk that the lock button could get damaged.
- 


7. Pull handle out to extend.
- 


8. Insert base board into cart and lay it flat.
- 


9. Use the 2 top side straps at the top for transporting folded umbrella.
- 

10. Use the centre handy straps to secure your open umbrella to cart.
- 


11. Before packing up, remove base board from cart
- 

12. Press the button at handle shaft base and push down handle.
- 

13. Lift the middle straps to fold cart up.
- 

14. Collapse in diagonal direction and compact to minimum size.
- 

15. Lay cart flat on the ground and rotate the front swivel wheels 90 degrees to insure a tight closure as image indicates. Then wrap base board around cart and secure.

Keep the base board above the handle hinge.
- 

16. Press yellow button to pull out wheels if necessary.

*Reminder: To maintain the performance of the wheels, if needed, tighten the nuts on the wheels.

200mm