



GEAR FOR LIFE

SEAT COVER INSTALLATION INSTRUCTIONS

CONGRATULATIONS ON YOUR PURCHASE

of your new Premium Canvas Seat Covers! When installed correctly, MSA 4X4 seat covers will not move and will provide long lasting comfort and protection for your vehicle's seats. To ensure you get a perfect fit, our seat covers are made extremely neat & tight. This means the fitting time may take a little longer.

Driver & passenger seats marked on the underside of seat cover (198)

TOYOTA LANDCRUISER 70/76/78 SERIES FRONT TWIN BUCKETS MODEL NO: LC707

1. Remove Headrest.
2. Undo all Velcro tabs and straps on side and base of seat cover.
3. Slide seat cover over upper rear of seat.
4. Pull down firmly and center on seat.
5. Reinstall headrest.
6. Push center flap through to rear and pull up firmly.
7. Reattach Velcro tab.
8. Place base cover over seat base and pull firmly towards rear.
9. Place straps inside of back adjust lever and inside seat belts.
10. Pull sides of cover down as firmly as possible, moving cover back and forth and tuck in behind any trims, pull both sides towards rear.
11. Attach front to back straps under seat and tension firmly.
12. Feed straps at rear through 3 loops and attach side release buckle and tension firmly.
13. On the inner side of both seats is another tension strap which needs to be fed carefully on top of seat runners and free from adjuster cables underneath base of seat and towards the rear. Attach extra side release buckle, pull firmly towards rear and tie straps if needed.
14. Ensure seat cover is a neat fit all round and adjust if necessary.